

One family that masters everything: SIPART PS100 and SIPART PS2

Reliable and flexible valve control

siemens.com/positioners

# From Basic to Premium: SIPART PS100 and SIPART PS2

### SIPART PS100 – the simple controller

Not all applications need an all-rounder like the fully-featured SIPART PS2. That's why we expanded our portfolio to give you the option of a new and highly efficient electropneumatic positioner, the SIPART PS100. It's the right choice whenever you need a simple, fast, and reliable controller for standard applications.

### Special features of the SIPART PS100:

- Quick to initialize
- Very robust and easy to operate



As the interface between the control system and valves, positioners play an important role in ensuring reliability and optimal performance in your automated process plants. With the proven SIPART PS2 – now with new features – and the new SIPART PS100, we offer two positioners that are just right for your applications and requirements.



# SIPART PS100 and SIPART PS2 – the choice is yours



Ease of use

Robust: non-contacting sensor, non-corrosive

**Environmentally friendly: low compress** 

Extendable: integrated booster, mo

Smart features: Fast Open/Fast

SIPART PS100



» One-push initialization: initialize at


» Device automatically adjusts to the

Quick to initialize

connected valve

the push of a button

### Easy selection of the control mode



» Maximum performance for every application



### Valve status at a glance

- » Screen symbols in accordance with NAMUR NE107
- » Local operation with large screen and four buttons



Animated video on the "ease of use" approach

SIPART PS100 or SIPART PS2 – you can make the choice that's right for you depending on your application. Whereas the main strength of the SIPART PS100 lies in its "ease of use" approach, flexibility is the name of the game with the SIPART PS2. We haven't cut any corners when it comes to the benefits they both offer.

### **Flexibility**

sound absorber, multiple enclosure variations

sed air consumption and CO2 emissions

ounting kits, pressure-gauge blocks

Close, leakage compensation



SIPART PS2





- » Integral pressure sensors monitor compressed air supply and valve chamber pressure
- » Stable control, even in case of pneumatic leaks or deposit buildups
- » Maintenance information on spring status, number of strokes, static friction affecting the gland seal, wear to the valve seat, and alerts in accordance with NE107



Animated video on diagnostic functions



#### Digitalization

- » Extensive control and diagnostic options using the valve monitoring app
- » Fast and predictive determination of valve maintenance requirements
- » Information transmitted to higherlevel maintenance systems



Animated video on valve monitoring app

# The future is digital

This refined positioner gives you the best possible support as you digitalize your processes.

Thanks to assessments using the Siemens valve monitoring app, SIPART PS2 provides you with end-to-end control and analysis options. This maintenance information can be transmitted to higher-level maintenance systems so you can plan and perform your maintenance activities predictively and flexibly adapt your service intervals to suit your requirements. The result is greater plant availability and reliability as well as maintenance costs you can plan for.



The valve monitoring app alerts you to potential deviations during operation and lets you plan maintenance activities in advance.



Maintenance schedules are clearly displayed and can be accessed anywhere.

## Two products with a lot in common

Lower CO<sub>2</sub> emissions and the right enclosures for your needs – the strengths of the SIPART devices include being environmentally friendly and very robust.

### **Extremely robust**

- » Non-contacting sensor
- » Non-corrosive sound absorber
- » Range of enclosure options

### **Environmentally friendly portfolio**

- » Low compressed air consumption
- » Reduced CO<sub>2</sub> emissions from compressors
- » Compressed air savings of up to 90 percent possible compared with traditional devices



The expanded functions of the SIPART positioners offer you all the benefits needed to ensure that you're optimally prepared for the challenges the market can throw your way.

These functions include the unique Fast Open/Fast Close technology, integrated boosters to adjust large valves quickly, and the compensation of leakage.





- » Faster valve adjustment thanks to smart chamber pressure control
- » Air isn't completely released from the valve, so a new operation point is reached more quickly
- » The result is a substantial reduction in costs



#### Integrated booster

- » Fast adjustment for large drives
- » Mounted directly on the positioner, reduces external tubing to a minimum
- » Software-supported initialization directly from the positioner



Animated video on fast valve adjustment



Animated video on integrated booster

## Designs in the SIPART family

The positioner: an all-rounder that optimally meets a wide variety of requirements, whether in compact form for many standard applications or in a remote version for specific applications.

#### **Compact positioners**





### Positioner with various external position detection systems

- Suitable for use in extreme ambient conditions, such as vibration
- Easier access to positioner for valves at not easily accessible locations
- Position detection available as standard solution or integrated in a robust aluminum enclosure



Want to know more about the SIPART PS100? Just scan the QR code to see the product video.



Be impressed by the SIPART PS2 all-rounder. Just scan the QR code to go to the product video.





### Positioner with remote control electronics

- Suitable for use in environmental conditions with high-energy radiation
- Easier access to control electronics through control cabinet
- Distance between control electronics and valve can be up to one kilometer



Technical data	SIPART PS100	SIPART PS2
Enclosure	Aluminum, aluminum/polycarbonate	Polycarbonate, aluminum, stainless steel
Premium diagnostics	No	Yes
Modules can be retrofitted	No	Yes
Limit values	No	2 (mechanical or capacitive)
Digital input/digital output	1 DI/1 DO	2 DI / 3 DO
External position detection	No	Yes
Communication	4 – 20 mA	4–20 mA, HART 7, PROFIBUS PA, FF
EX certificates	No	• ATEX, IEC: Ex i, ec, t, Ex d • FM, CSA: IS, NI/I/2, DIP, XP
Ambient air temperature	−20 +80 °C, −4 +176 °F	-30 +80 °C, Option: −40 °C, -22 +176 °F, Option: −40 °F
SIL	No	Yes

### Published by Siemens AG

Process Industries and Drives Östliche Rheinbrückenstr. 50 76187 Karlsruhe Germany

Article No.: PDPA-B10459-00-7600 Dispo 27900 WS 11184.0 Printed in Germany © Siemens AG 2018

Subject to changes and errors. The information provided in this brochure contains descriptions or performance characteristics which, in case of actual use, do not always apply as described or which may change as a result of further development of the products. The desired performance characteristics are only binding if expressly agreed in the contract. Availability and technical specifications are subject to change without notice.

All product designations may be trademarks or product names of Siemens AG or supplier companies, the use of which by third parties for their own purposes may violate the rights of the owners.

